

Government of Pakistan PAKISTAN ORDNANCE FACTORIES TENDER ENOUIRY

То	M/s	TENDER ENQUIRY
Dear	Sirs,	
		rence: TENDER ENQUIRY NO. <u>0201/LP/FILL/54</u> You are requested to submit quotations for the item(s) noted in the Schedule to Tender. Please note the following instructions for filling the tender:-
1. St	JBMISS:	ION OF TENDER
1.1	Hall, <u>www.e</u> minut	ebidding.pof.gov.pk as well as in hard form (duly sealed in envelope) before 30 tes of opening time. The tender received late will not be entertained. You may ess the opening of the tender if you so desire. If a representative is deputed, he
		(www.ebidding.pof.gov.pk) BID CENTER
		ADJACENT TO RABITA HALL
		POFs, WAH CANTT.
2. <u>G</u>	ENERAL	INSTRUCTIONS REGARDING PREPARATION OF QUOTATIONS
2.1	the	Materials, the prices should be filled in column 5 and delivery date in column 7 of schedule to this Tender Enquiry. As per PPRA Rule 36(b), Single Stage two
	& co	<pre>lope method will be utilized for "Open competitive bidding." Moreover, technical mmercial evaluation of Bids will be carried out strictly as per PPRA rules and ract(s) will be awarded to the most advantageous bidder(s).</pre>

2.2 For Plant and Machinery, you are required to quote in two parts: Part I "Technical Offer": It should exclusively give technical details and
 literatures/brochures of the offered plant, machinery and equipment; validity date;
 delivery schedule; and signed undertaking given on the schedule to this Tender Enquiry.

It must not indicate price, costs etc.

-2- **POF 1262-A**

Part II "Commercial Offer": It should indicate the commercial terms e.g.price, terms of payment, mode of payment, mode of supply.

- 2.3 The quotation must remain valid for, at least 90 days from the date of opening of commercial tenders, extendable if so desired.
- 2.4 The quotation should hold good for any reduced or enhanced quantities without notice.
- 2.5 In the event of non-acceptance of offer, intimation may be given to the Tenderers on their request.
- 2.6 Conditional offers or alternative offers are likely to be ignored.
- 2.7 Quotations should be based on:-
 - F.O.R. station of dispatch basis, i.e. delivered free on rail, inclusive of packing and forwarding charges. The stores will be booked under Military Credit Note, to be provided by the purchaser.

and/or

Free delivery at POF's stores at **WAH CANTT**In this case Octroi duty, will be payable by the supplier.

- 2.8 Taxes and Duties etc. where applicable, must be shown separately, quoting refrences to Registration No. in cases of Sales Tax and relevent authority in the case of others. Offers without these clarifications and inclusive of Taxes and Duties may be ignored.
- 2.9 Taxes and duties levied on or after Tender opening date or on or after the date offer was signed and dispatched will be allowed to include in the offered rates.
- 2.10 "Suppliers will furnish a certificate, issued by Excise & Taxation deptt:, that he has cleared all Proffessional Tax payable by him" offers recieved without this certificate will be rejected.
- 2.11 Suppliers will render necessary information regarding hazardous effects on environment, of the material/products supplied by them, in their quotations and shipping/dispatch documents.
- 2.12 If the requisite information is not furnished on the T.E forms or offer received is not conformity with the requirement of the T.E such offer shall be ignored.

3. INSPECTION

- 3.1 Supplies shall be subject to the inspection and acceptance by the competent inspection authority nominated by the Purchaser, who will arrange it at his own cost. Inspection facilities such as tools, test equipment, instruments etc will, however, be provided by the Suppliers in accordance with the relevant specifications.
- 3.2 Where considered necessary by the Purchaser, stores may be obtained on Warranty/Guarantee subject to inspection on receipt. Rejected stores will be removed and replaced with the acceptable stores by the Supplier at his own expense, within a specified time.

-3-POF 1262-A

4. TENDER FEE

The tender must be accompanied by a copy of non-refundable fee by means of a crossed postal order/pay order for Rs. 500/- in favour of: **Director-Admin-POFs**, **Wah Cantt**. The tender fee instrument in original must be provided on day/date of tender opening in the Bid Center.

4.1 TENDER SAMPLE

Where required, offer must accompany tender sample., strictly according to the description and specification given in Tender Enquiry. Offer not accompanied by tender sample will NOT be entertained excepting the established and reputable firms who have either previously satisfactorily supplied the same or similar stores or have submitted an acceptable sample thereof against previous T.E.

5. BID Security

5.1 A copy of Bid Security should accompany the tender in shape of deposit at call receipt/Pay Order/Banker Cheque from scheduled bank drawn in favour of :-

GM PP&C FILLING

- 5.2 Bid security instrument in original must be provided on the day/date of tender opening in the Bid Center as under:
 - a. Registered/indexed firms including foreign firms 2% of quoted value subject to the maximum ceiling of Rs. 0.5 Mn.
 - b. Registered/un-indexed firms including foreign firms 3% of quoted value subject to the maximum ceiling of Rs. 0.75 Mn.
 - c. Unregistered Firms including foreign firms 5% of quoted value subject to the maximum ceiling of Rs. 1.00 Mn.
 - d. Govt organization/production units/state owned enterprises/welfare projects of Svcs HQ Rs 0.50 M. can be waived off on request by DG(C)
 - e. Bid money will be returned to unsuccessful (less first three lowest quotee firms) bidders on opening of commercial offers
 - f. Bid money will be returned to successful bidders on submission of performance bond/unconditional B.G.
 - g. Quotation accompanied with less bid money will be accepted on provisional basis for $10\ x$ days after opening of bids. However the firms are bound to provide/furnish the balance bid money within $10\ x$ days after opening of bid otherwise such quotations will be ignored or rejected
 - h. Offers received without Bid Security will not be entertained.
 - i. Bid money will be forfeited in case the quotation is withdrawn before the expiry of its validity date.

6. ACCEPTANCE OF OFFERS

6.1 POF may reject all bids or proposals at any time prior to the acceptance of bid(s) or proposal, but is not required to justify grounds for its rejection. POF shall incur no liability towards supplier or contractor who have submitted bids or proposals.

6.2 PERFORMANCE BOND

- (a) The successful bidders shall provide performance bond which shall not exceed 10% of contract value, in the form of Deposit At Call Receipt from a scheduled Bank; or, an un-conditional Bank Guarantee on a prescribed format. The performance Bond will be in favour of C.M.A.(POF) Wah Cantt. It will be returned on satisfactory completion of contract.
- (b) If the Supplier fails to furnish the Performance Bond within the specified time, such failure will constitute a breach of the contract and the Purchaser shall be entitled to make other arrangements for purchase of the stores at the risk and expense of the Supplier.

POF 1262

-4-

6.3 Performance Bond from State owned organizations may be waived off at the discretion of the Purchaser.

6.4 FAILURE TO SUPPLY THE STORES

All deliveries must be completed by the specified date. In case of failure to deliver the stores within the scheduled time should have arisen from "Force Majeure", which the purchaser may admit as reasonable ground for further time, he will allow such additional time as he may consider to have been required by the circumantances of the case.Otherwise, he will be entitled, at his discretion, to cancel the contract; and/or claim liquidated damages upto 2% but not less than 1% of the contract price of the items and their quantities for each and every month or part of a month, beyond the specified delivery date, during which these may not be delivered, subject to a maximum of 10% of the total contract value of the particular stores which remained unsupplied either in part or in full: or, to purchase from elsewhere, the unsupplied stores at the risk and cost of the supplier.

6.5 PAYMENT

Payment will be made by the CMA(POF) through crossed cheque on receipt/acceptance of stores on our prescribed bill form supported by receipt voucher on part/full supply basis.

(a) Payment of duties/Taxes including professional tax (where applicable) must be supported by proof of having paid these to concerned Govt. Taxation Deptt.

7. SECURITY OF INFORMATION

The tenderer and his employees must not communicate any information relating to the sale/purchase of stores under this enquiry to any person other than the manufacturer or to any press or agent not authorised in writing by POFs to receive it.

Please return the Schedule to the Tender duly signed by the specified date, alongwith the specifications, drawings etc.if any, enclosed herewith – even if you are unable to $$\operatorname{\mathsf{quote}}$.$

<u>WARNING</u> In case the firm abstain from making offers or fail to return/acknowledge the tender form by the specified date on three consecutive occasions, no further tender enquiry may be issued to them and their names would liable to removed from the approved list.

Yours faithfully

SUMAIRA YAMIN MANAGER PURCHASE FILL

for PAKISTAN ORDNANCE FACTORIES

PAKISTAN ORDNANCE FACTORIES

SCHEDULE TO TENDER NO. 0201/LP/FILL/54

17-OCT-24

(1) FOR MATERIALS

(1)	(2)	(3)	(4)	(5)	(6)	(7)
Item No.	Description with Specs. etc.	Unit	Qty	Quoted Value	Price Per Unit FOR or free delivery	Delivery Date
					In Figures In Words	

1	CEMENT RD-1151-B LEAD FREE SPEC NO.	KG	65	
	CS-2752-B			IMMEDIATE
2	CEMENT RD-1279	KG	80	
				IMMEDIATE

Total Rs =	
+ GST =	
Total value Rs =	

(2) For Plant & Machinery:
 Specification:-

(3) Special Conditions

- (1) Required Delivery period: 03 Months after placement of contract.
- (2) Inspection of store will be carried out by Director QA POF Wah Cantt and 05% Super check by user section.
- (3) Firms registered with Sales Tax and Income Departments who are on Active Taxpayers List (ATL) of FBR are eligible to participate in the bid. Documentary proof of the same must be attached with the bid.
 - (4) Participating firms must confirm TE spec. Parameters
- (5) The tender received without electronic means will not be entertained. You may witness the opening of tender if you so desire. If a representative is deputed, he should bring a letter of authority.
- (6) Hard copy of both technical & financial quotations must also be reached to Bid Centre before tender opening. Photocopy of bid money hiding the amount must be accompanied with technical quotation.
 - (7) Validity period will be considered after opening of commercial offer.
- (8) Quotation must remain valid at least for 90 days from date of commercial opening and should hold good for any reduced or enhanced quantity.
- (9) Photocopy of NTN & PTC Certificate duly attested by Gazetted Class-I Officer must be attached with the bid.
- (10) Participating firms should have not defaulted in any contract with POF or any other govt. organization.
- (11) Bids will be opened as per PPRA Rule 36 (b) "Single Stage-Two Envelope Procedure" in which the bid shall comprise of two separate envelopes: Technical proposal and commercial proposal. Initially only Technical Offer will be opened.
 - (13) Price escalation clause is not allowed. No fax or e-mail offer will be accepted.
- (14) Supplier must accept all the terms and conditions embodied in the form POF 1281 (General conditions of contract) and in T.E general instructions Performa form POF 1262 A (indigenous supplies).
- (15) Rates and sales Tax must be shown separately otherwise rate will be considered inclusive of G.S.T.
- (16) Please clearly confirm our specs / drawing. Conditional or alternative offers are likely to be ignored.
- (17) The store must be protected adequately and appropriately against damages from environmental effects, water or other substances during journey/transportation to withstand the rough handling involved in the transit and provide preservation of store while held in the storage by the supplier.

PAKISTAN ORDNANCE FACTORIES

SCHEDULE TO TENDER NO. 0201/LP/FILL/54

17-OCT-24

(1)	(2)	(3)	(4)	(5)	(6)	(7)
Item No.	Description with Specs. etc.	Unit	Qty	Quoted Value	Price Per Unit FOR or free delivery	Delivery Date
.					In Figures In Words	

- (18) Any quantity of store, if found defective functionally will essentially be replaced by the supplier free of cost under his own arrangements
 - (19) Material Safety Data Sheet (MSDS) may be provided at the time of supply.

Undertaking

Should our offer be accepted, we hereby undertake to supply the stores/render the services contracted on the basis of General Conditions of Contract embodied in Form POF 1281, and to deposit the performance bond within the prescribed time, failing which it will constitute a breach of contract, and POF will have the right to purchase the stores/services elsewhere at our risk and cost.

Place	Signature of the	Tenderer	
Date	Name		
	Position		
	Address		
	Income Tax G.I.R	. No	
	Official Stamp		

CEMENT R.D. 1151B "LEAD FREE"

Specins 386

Specification to govern supply and inspection

Date of Approval 21.6.1954

1. SCOPE

This specification relates to a waterproof solvent comont for use on screw threads.

2. RELATED DOCUMENTS

(a) Reference is made in this specification to:-



(i) British Standards

B.S.410 "Test Sievos"
B.S.508 "n-Butanol"
B.S.756 "Doan and Stark Apparatus"
B.S.1733 "Flow Cups and Methods of Use"

(ii) C.S. Specifications

C.S.1540 "Asphaltic Bitumen, lead-free"
C.S.1669 "Copal Eater Gum, lead-free"
C.S.1987 "Normal Propyl Gallate (Anhydrous)"
C.S.1988 "Oiticid Oil lead-free"
C.S.2753 "Red Oxide of Iron, Manufactured, lead-free"
C.S.3015 "Xylole, 50 lead-free"

(b) Any reference in this specification to a British Standard or C.S. Specification, undated, means, in any tender of contract, the latest edition of that document current at the date of the tender or contract.

3. COMPOSITION

(a) The Coment shall be homogeneous, from foreign matter and visible impurities, and shall consist of the following ingredients in the proportions stated:-

Ingredient	Parts by weight
Asphaltic Bitumon, laad-free	10
n-Butanol	2
Copal Ester Gum, low-free	20
Oiticica Oil, load-frac	0.24
n-Propyl Gallate (anhydrous)	0.01
Red Oxide of Iron, Manufactured,	
Xylole, 5° lead-free	(approx.) 18

The proportion of Xylole 5° chould be adjusted, if necessary, in order that the finished material shall comply with the requirements of sub-clause 6(d) below.

- (b) The ingredients, other than the n-Butanol, shall comply with the requirements of the relevant current approved C.S. specifications listed in sub-clause 2.a above. The n-Butanol shall comply with British Standard 508.
- NOTE: Attention is drawn to the note regarding volatile matter content in the specification governing red oxido of iron, manufactured; failure to conform thereto may result in production of unsatisfactory coment.

MANUFACTURE

The method of manufacture adopted shall be such that the finished material complies in every respect with the requirements of this specification.

NOTE: For the guidance of manufacturors, details of a method which has produced a satisfactory cement are given in Appendix A.

SAFETY OF OPERATIONS

Nothing in this specification shall relieve the Contractor of his responsibility for the safety of his operations.

TESTING

Samples taken from any portion of the supply shall comply with the following requirements:-

(a) Gonoral

The material shall comply with the requirement of clause 3 above.

(b) Freedom from Coarse Particles and Grit

- (i) Coarse particles. The material shall be wholly capable of being washed through a No. 60 B.S. Sieve using hot Xylole 5°.
- (ii) Grit. When determined in the manner described in Appendix B, the grit content of the material capable of retention by a No. 240 B.S. Sieve shall not exceed 0.05 per cent by weight.

(c) Water Content

The water content of the material, determined with a Dean & Stark apparatus having a 2 ml. type 1 receiver and conforming to B.S.756:1952, shall not exceed 0.4 per cent by weight.

(d) Viscosity

When tested at 25°C by the method described in B.S.1733 and using a type A.15, B.S. flow cup, the time of flow shall not be less than 35 seconds nor greater than 60 seconds.

(e) Freedom from Lead

The material shall not contain lead or compounds of lead, calculated as metallic lead, together exceeding 0.03 per cent.

Amendment C dated 29.11.6

Any question that may arise relative to this specification should be referred to the Director of Chemical Inspection, The War Office

POLYSTYRENE CEMENTS AND VARNISHES

RD. 1212A, RD. 1221A, RD. 1276A and RD. 1279

Date of approval 17th October, 1955

145

This specification covers the supply of certain cements and varnishes based on polystyrene armament purposes.

ATED DOCUMENTS

Reference is made in this specification to:-

- (i) British Standard 188,
- 'Methods for the determination of the viscosity of liquids in c.g.s. units!
- (11) British Standard 458,
- 'Xylenes'. 'Trichloroethylene'.
- (iii) British Standard 580, (iv) British Standard 805, (v) British Standard 1940, (vi) British Standard 1999,
 - 'Toluenes'.
- 'Ethyl methyl ketone (methyl ethyl ketone)'. 'Tritolyl phosphate'.
- (vii) Specification DEF-1053,
- 'Standard methods of testing paint, varnish, lacquer and related products'.

TARREST OF

- (viii) Specification C.S. 1843,
- (viii) Specification C.S.1843, 'Dyes for shellar lacquers'.

 (ix) Specification C.S.2803, 'Polystyrene material'. Reference in this specification to a British Standard undated, a DEF or C.S. specification, means, in any tender or contract, the edition current at the date of such tender or contract.

FORMATION TO BE SUPPLIED BY THE PURCHASER

The purchaser shall state clearly in his order which cement or varnish is required and hether it is to be coloured or clear.

The cement or varnish shall be propored from the ingredients in the proportions by weight ahown:-

INGREDIENTS	VARNISH RD.1212A	CEMENT RD.1221A	VARNISH RD.1276A	CEMENT RD.1279
Polystyrene material for	9	25	一個社会	
armament compositions	0	23	· 图 · ·	2
Tritolyl phosphate	-	3	8	7
Coumarone resin	-	-	8.	70-19
*Dye oil orange	- A.W.		0.25	
Solvent red 51	-	0.5	-	0.2
Ethyl methyl ketone		75	76	
Toluene	- 3	- 200	-	72
50 Xylene	2	- 3		
Chlorinated paraffin wax		11/21/2009		
(Cereclor 1)	2	- 400	4	第二次
Trichlorosthylene, type 2	88	- 400	12-12-86	Table 1

^{*}Dyestuff to be added if sement or varnish is required to be coloured.

MATERIALS USED IN MANUFACTURE

The ingredients used for these compositions shall comply with the appropriate ourrent approve specifications and any additional requirements, as shown below:-

Toluene B.S.805/1	題
Ethyl methyl ketone B.S.1940	
5° Xylene B.8.458/4	
Trichloroethylene, type 2 B.S.580	超
Dye, oil orange C.S.1843	S.
Polystyrene material for armament compositions, lead free C.S.2803	
Coumarone resin C.460 obtainable from British Resin Products Ltd.	
Chlorinated paraffin wax (Cereolor 1) obtainable from I.C.I. Ltd.	
Solvent red 51 - Orașol brilliant fast red RG obtainable from Clayton Dyestuffs Co. Ltd	

Tritolyl phosphate shall comply with the requirements of B.S. 1999 except that the acidity when determined as described in Appendix C of the Standard shall not be greater than 0.01 per cent.

6. MANUFACTURE

The ingredients shall be agitated in a closed vessel until solution is complete. The viscosit of the solution shall be adjusted by addition of the appropriate solvent to comply with the requirements of sub-clause $\theta(c)$ but the volatile matter shall remain within the limits stated in sub-clause $\theta(b)$.

7. SAFETY OF OPERATIONS

Nothing in this specification shall relieve the contractor of his responsibility for the safety of his operations.

8. TESTING

- (a) General. The cement or varnish shall comply with the appropriate composition set out in clause 4 and shall be in the form of a clear liquid, free from sediment or suspended matter.
- (b) Volatile matter. The percentage loss in weight when a known quantity of the material is dried to approximately constant weight at 100 ±5°C shall be recorded as the volatile matter, and shall be within the limit specified for the appropriate composition in the table below.
- (c) Viscosity. The viscosity of the material determined at 25±0.5°C in accordance with B.3.188 shall fall within the range specified for the appropriate composition in the table below.
- (d) Drying time. When the material is flowed on to a tin-plate sheet at a temperature of 15.5-21°C (60-70°F) and is allowed to drain in a vertical position at that temperature, it shall become dry within the time specified for the appropriate composition in the table below when tested according to specification DEF-1053, Method No. 7.

	VARNISH	CEMENT	VARNISH	CEMENT
	RD.1212A	RD, 1221A	RD.1276A	RD.1279
Volatile matter (sub-plause 6b)	Not greater than 92 per cent	Not greater than 80 per cent	Not greater than 82 per cent	69-73 per cent
(sub-clause 8c)	55-55	180-290	7-11	710-930
	centistokes	centistokes	centistokes	centistokes
Drying time (sub-clause 8d)	Not greater than 10 minutes	Not greater than 5 minutes	Not greater than 5 minutes	Not greater than 10 minutes

(e) Freedom from lead. The material shall not contain lead or lead compounds, calculated as metallic lead, together in excess of 0.03 per cent.